



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

1. IDENTIFICATION

Product Name	Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)
Other Names	Potassium Acetate
Recommended use of the chemical and restrictions on use	
Identified uses	Fire Extinguishing Agent
Restrictions on use	Consult applicable fire protection codes
Company Identification	Badger Fire Protection 944 Glenwood Station Lane, Suite 303 Charlottesville, VA 22901 USA
Customer Information Number	(434)-964-3200
Emergency Telephone Number	
CHEMTREC Number	(800) 424-9300 (703) 527-3887 (International)
Issue Date	April 10, 2015
Supersedes Date	February 9, 2015

Safety Data Sheet prepared in accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

2. HAZARD IDENTIFICATION

Hazard Classification

This product is classified as not hazardous in accordance with the Globally Harmonized System of Classification and Labelling (GHS).

Label Elements

Hazard Symbols
None

Signal Word: None

Hazard Statements

None

Precautionary Statements

Prevention

None

Response

None

Storage

None

Disposal

None



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

2. HAZARD IDENTIFICATION

Other Hazards

None

Specific Concentration Limits

The values listed below represent the percentages of ingredients of unknown toxicity.

Acute oral toxicity	0%
Acute dermal toxicity	0%
Acute inhalation toxicity	0%
Acute aquatic toxicity	0%

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a substance.

Component	CAS Number	Concentration
Potassium Acetate	127-08-2	~100%

4. FIRST- AID MEASURES

Description of necessary first-aid measures

Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if irritation persists.

Ingestion

Dilute by drinking large quantities of water and obtain medical attention.

Inhalation

Move victim to fresh air. Obtain medical attention immediately for any breathing difficulty.

Most important symptoms/effects, acute and delayed

Aside from the information found under Description of necessary first aid measures (above) and Indication of immediate medical attention and special treatment needed, no additional symptoms and effects are anticipated.

Indication of immediate medical attention and special treatment needed

Notes to Physicians

Treat symptomatically.

5. FIRE - FIGHTING MEASURES

Suitable Extinguishing Media

This preparation is used as an extinguishing agent and therefore is not a problem when trying to control a fire. Use extinguishing agent appropriate to other materials involved.



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

5. FIRE - FIGHTING MEASURES

Specific hazards arising from the chemical
None known

Special Protective Actions for Fire-Fighters
Wear full protective clothing and self-contained breathing apparatus as appropriate for specific fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures
Wear appropriate protective clothing. Prevent skin and eye contact.

Environmental Precautions
Prevent large quantities of the material from entering drains or watercourses.

Methods and materials for containment and cleaning up
Sweep up or vacuum and transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling
Wear appropriate protective clothing. Prevent skin and eye contact.

Conditions for safe storage
Store containers away from high heat sources. Storage area should be: - cool - dry - well ventilated - under cover - out of direct sunlight

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
Exposure limits are listed below, if they exist.

Potassium Acetate

None

Nuisance Dust Limit

OSHA PEL: 50 mppcf or 15 mg/m³ TWA, total dust
15 mppcf or 5 mg/m³ TWA, respirable fraction

Appropriate engineering controls

Use with adequate ventilation. There should be local procedures for the selection, training, inspection and maintenance of this equipment. When used in large volumes, use local exhaust ventilation.

Individual protection measures

Respiratory Protection

Not normally required. Use dust mask where dustiness is prevalent, or TLV is exceeded. In oxygen deficient atmospheres, use a self contained breathing apparatus, as an air purifying respirator will not provide protection.



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin Protection

Gloves

Eye/Face Protection

Chemical goggles or safety glasses with side shields.

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State	Solid (powder)
Color	White
Odor	Odorless
Odor Threshold	Not applicable
pH	Not applicable
Specific Gravity	1.57
Boiling Range/Point (°C/F)	No data available
Melting Point (°C/F)	292/558
Flash Point (°C/F)	Not flammable
Vapor Pressure	Not applicable
Evaporation Rate (BuAc=1)	Not applicable
Solubility in Water	200g/100g water
Vapor Density (Air = 1)	Not applicable
VOC (g/l)	None
VOC (%)	None
Partition coefficient (n-octanol/water)	No data available
Viscosity	No data available
Auto-ignition Temperature	Not applicable
Decomposition Temperature	No data available
Upper explosive limit	Not applicable
Lower explosive limit	Not applicable
Flammability (solid, gas)	Not flammable

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Exposure to direct sunlight - contact with incompatible materials



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

10. STABILITY AND REACTIVITY

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products

Oxides of carbon - potassium

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Potassium Acetate

Oral LD50 (Rat) 3250 mg/kg

Dermal LD50 (Rabbit) >20,000 mg/kg (analogous compound)

Inhalation LC50(rat) >5.6 mg/l (analogous compound)

Specific Target Organ Toxicity (STOT) – single exposure

Potassium Acetate: No data available

Specific Target Organ Toxicity (STOT) – repeat exposure

Potassium Acetate: No data available

Serious Eye damage/Irritation

Potassium Acetate: Not irritating (rabbit)

Skin Corrosion/Irritation

Potassium Acetate Not irritating (rabbit)

Respiratory or Skin Sensitization

Potassium Acetate: Available data indicates this component is not expected to cause skin sensitization. No data available for respiratory sensitization.

Carcinogenicity

Not considered carcinogenic by NTP, IARC, and OSHA.

Germ Cell Mutagenicity

Potassium Acetate: Available data indicates this component is not expected to be mutagenic.

Reproductive Toxicity

Potassium Acetate: Available data indicates this component is not expected to cause reproductive toxicity or birth defects.

Aspiration Hazard

Not an aspiration hazard.



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

12. ECOLOGICAL INFORMATION

Ecotoxicity

Potassium Acetate:

LC50 Zebrafish 1497 mg/l 96h

EC50 Daphnia magna 420 mg/l 48h

EC50 Mann diatom 500 mg/l 72hr

Mobility in soil

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bioaccumulative Potential

No relevant studies identified.

Other adverse effects

No relevant studies identified.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of container in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Safety Data Sheet information is intended to address a specific material and not various forms or states of containment. Specific volumes, pressures or hardware configurations containing such materials can dictate various different hazard classifications for transportation and labelling requirements. Under Federal Regulations only trained and qualified individuals are permitted to label and ship products following the applicable Department of Transportation (DOT), Federal Aviation Administration (FAA), Transport Canada (TC), International Maritime Dangerous Goods (IMDG) or International Air Transport Association (IATA) requirements.

15. REGULATORY INFORMATION

United States TSCA Inventory

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Substance Inventory.

Canada DSL Inventory

All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL) or are exempt from listing.

SARA Title III Sect. 311/312 Categorization

None

SARA Title III Sect. 313

This product does not contain any chemicals that are listed in Section 313 at or above de minimis concentrations.



SAFETY DATA SHEET

Loaded Stream (Anti-Freeze) AC-40 Dry Charge (Fire Extinguishing Agent)

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Health - 1
NFPA Code for Flammability - 0
NFPA Code for Reactivity - 0
NFPA Code for Special Hazards - None

HMIS Ratings

HMIS Code for Health - 1
HMIS Code for Flammability - 0
HMIS Code for Physical Hazard - 0
HMIS Code for Personal Protection - See Section 8
*Chronic

Legend

ACGIH: American Conference of Governmental Industrial Hygienists
CAS#: Chemical Abstracts Service Number
EC50: Effect Concentration 50%
IARC: International Agency for Research on Cancer
LC50: Lethal Concentration 50%
LD50: Lethal Dose 50%
N/A: Denotes no applicable information found or available
OSHA: Occupational Safety and Health Administration
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit
TLV: Threshold Limit Value
TSCA: Toxic Substance Control Act

Revision Date: April 10, 2015
Replaces: February 9, 2015
Changes made: Updated to GHS Classification.

Information Source and References

This SDS is prepared by Hazard Communication Specialists based on information provided by internal company references.

Prepared By: EnviroNet LLC.

The information and recommendations presented in this SDS are based on sources believed to be accurate. Badger Fire Protection assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the material for their particular purposes. In particular, we make **NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED**, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use or disposal of the material is in accordance with applicable Federal, State, and local laws and regulations.